SCOPE OF ACCREDITATION TO ISO/IEC 17025:2017

ELEMENT MATERIALS TECHNOLOGY CANADA INC.*
Mississauga Laboratory
2395 Speakman Drive
Mississauga, Ontario, Canada L5K 1B3
Luiz Rios Phone: 905-822-4111 ext. 10282

Test Method:	**Test Description:**
AAMA 1304	Voluntary specification for forced entry resistance of side-hinged door systems
AAMA 1503	Voluntary test method for thermal transmittance and condensation resistance of windows, doors and glazed wall sections (CRF only)
ANSI Z97.1	

Test Method:

Test Method:	Test Description:
CGSB 75.1-M88	Tile - cerami i9 Tw 10.98 -0o52 650.98 -0 s0598 -0 0 10.98 231.54 6(0.4

Test Method:	**Test Description:**
CAN/ULC S711.1	Standard for thermal insulation – bead-applied two component polyurethane air sealant foam - part 1: material specification (except C177 and E514)
CAN/ULC S711.2	Standard for thermal insulation – bead-applied two component polyurethane air sealant foam – part 2: installation
CAN/ULC S712.1	Standard for thermal insulation - light density - open cell spray applied semi-rigid polyurethane foam - material specification
CAN/ULC S743.1	STANDARD FOR THERMAL INSULATION – LOW PRESSURE APPLIED TWO COMPONENT SPRAY POLYURETHANE FOAM, PART 1: MATERIAL SPECIFICATION
CAN/ULC S770	Standard test method for determination of long-term thermal resistance of closed-cell thermal insulating foams
ICC ES AC02	Reflective insulation (test methods referenced in sections 3.0)